

Product family datasheetPARATHOM DIM LED PIN G9

Special LED lamps



 Atmospheric accent lighting throughout the home Shops, hotels and restaurants Foyers, offices Outdoor applications only in suitable luminaires

- Very long lifetime of up to 25,000 h Very low energy consumption Ideal for decorative and free-burning applications
- Product features LED alternative to high voltage halogen lamps Dimmable (with many common dimmers, see also www.ledvance.com/dim) Mercury-free lampsProduct benefits Very long lifetime of up to 25,000 h Very low energy consumption Ideal for decorative and free-burning applicationsAreas of application Atmospheric accent lighting throughout the home Shops, hotels and restaurants Foyers, offices Outdoor applications only in suitable luminairesReferences / LinksFor further products and actual information concerning LED lamps see www.ledvance.com/ledlampsFor Guarantee see www.ledvance.com/guarantee



Product family datasheet

Technical data


	Electrical data		Photometrical data			Light technical data	Dimensions & weight
Product description	Nominal wattage	Nominal voltage	Nominal luminous	Rated color	Light color	Starting time	Overall length
P DIM PIN 4.4 W/827 G9 ¹⁾	4.40 W	220240 V	flux 470 lm	temperature 2700 K	(designation) Warm White	< 0.5 s	59.0 mm
P DIM PIN 32 3.5 W/827 G9 ¹⁾	3.50 W	220240 V	350 lm	2700 K	Warm White	< 0.5 s	58.0 mm


	Lifespan				Additional product data	Capabilities	Certificates & standards
Product description	Nominal lamp life time	Rated lamp life time	Number of switching cycles	Lumen maintenance at end of service life	Base (standard designation)	Dimmable	Energy efficiency class
P DIM PIN 4.4 W/827 G9 ¹⁾	25000 h	25000 h	100000	0.70	G9	Yes	A++
P DIM PIN 32 3.5 W/827 G9 ¹⁾	25000 h	25000 h	100000	0.70	G9	Yes	A++

		Country specific categorizations		
Product description	Energy consumption	Order reference	ILCOS	
P DIM PIN 4.4 W/827 G9 ¹⁾	5 kWh/1000h	LEDPPIN40D 4,4W		
P DIM PIN 32 3.5 W/827 G9 ¹⁾	4 kWh/1000h	LEDPPIN32D CL 3	DRT/C-3,5/827-220- 240-G9-20/58	

¹⁾ All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Product family datasheet





P DIM PIN 4.4 W/827 G9

P DIM PIN 32 3.5 W/827 G9

Application advice

For more detailed application information and graphics please see product datasheet.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075271791	P DIM PIN 4.4 W/827 G9	Shipping carton box 20	150 mm x 122 mm x 77 mm	1.41 dm³	376.00 g
4058075811553	P DIM PIN 32 3.5 W/827 G9	Shipping carton box 20	150 mm x 122 mm x 77 mm	1.41 dm³	336.00 g

Product family datasheet

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
1 Todact code	i roduct description	rackaging ant (rieces/onit)	Dimensions (tength x width x height)	Votaine	Gross Weight

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For further products and actual information concerning LED lamps see

www.osram.com/ledlamps

For Guarantee see

www.osram.com/guarantee

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner of LEDVANCE of LAMPS



OSRAM GmbH Marcel-Breuer-Strasse 6 80807 Munich, Germany