

# Product family datasheet

## SubstiTUBE Split Control Ultra Output EM

LED tubes for electromagnetic control gears



- General illumination within ambient temperatures from –20...+50 °C Illumination of production areas Traffic zones and corridors Supermarkets and department stores

- No bending thanks to glass technology Quick, simple and safe replacement without rewiring Energy savings of up to 63 % (compared to T8 fluorescent lamp on CCG) Instant-on light, therefore ideally suitable in combination with sensor technology Very high resistance to switching loads Also suitable for operation at low temperatures Support the implementation of the HACCP concepts from production through to presentation High luminous flux for sophisticated lighting tasks Helps to prevent contamination in sensitive production areas (e.g. in the food industry)
- Product features Lamp tube made of glass with splinter protection (according to IEC 61549 AMD 2:2010 -810-1 4.4.1) LED alternative to classic T8 fluorescent lamps in CCG luminaires Rotatable end caps For especially uniform illumination Lifetime: up to 60,000 h Mercury-free and RoHS compliant Type of protection: IP20 Product benefits No bending thanks to glass technology Quick, simple and safe replacement without rewiring Energy savings of up to 63 % (compared to T8 fluorescent lamp on CCG) Instant-on light, therefore ideally suitable in combination with sensor technology Very high resistance to switching loads Also suitable for operation at low temperatures Support the implementation of the HACCP concepts from production through to presentation High luminous flux for sophisticated lighting tasks Helps to prevent contamination in sensitive production areas (e.g. in the food industry) Shatter protection thanks to special PET coating Areas of application General illumination within ambient temperatures from –20...+50 °C Illumination of production areas Traffic zones and corridors Supermarkets and department stores Equipment / Accessories Suitable for operation with low-loss and conventional control gears Legal advice When used to replace a T8 fluorescent lamp the total energy efficiency and light distribution depends on the design of the lighting system. Safety advice Not suitable for operation with electronic control gear. Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.



## Product family datasheet

### Technical data

	<b>Additional product data</b>
<b>Product description</b>	<b>Appropriate disposal acc. to WEEE</b>
ST8SPS 22.5 W/840 1500 mm	Yes

### Equipment / Accessories

- Suitable for operation with low-loss and conventional control gears

### Application advice

For more detailed application information and graphics please see product datasheet.

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075048157	ST8SPS 22.5 W/840 1500 mm	Shipping carton box 10	1652 mm x 210 mm x 115 mm	39.90 dm <sup>3</sup>	3640.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner  
of LEDVANCE of LAMPS

**OSRAM**

OSRAM GmbH  
Marcel-Breuer-Strasse 6  
80807 Munich, Germany