

Product family datasheet SubstiTUBE U-Shape

U-shaped LED tubes for electromagnetic control gears

- Street and city lighting Industry

- Quick, simple and safe replacement without rewiring Energy savings of up to 65 % (compared to T8 fluorescent lamp on CCG) Instant-on light, therefore ideally suitable in combination with sensor technology Very high resistance to switching loads Also suitable for operation at low temperatures
- Product features Double-capped LED alternative to classic T8 U-shaped fluorescent lamps in CCG luminaires Uniform illumination Mercury-free and RoHS compliant High luminous efficacy: up to 137 lm/W Lifetime: up to 50,000 h Type of protection: IP20Product benefits Quick, simple and safe replacement without rewiring Energy savings of up to 65 % (compared to T8 fluorescent lamp on CCG) Instant-on light, therefore ideally suitable in combination with sensor technology Very high resistance to switching loads Also suitable for operation at low temperaturesAreas of application Street and city lighting IndustryEquipment / Accessories Suitable for operation with low-loss and conventional control gearsLegal adviceWhen used to replace a T8 fluorescent lamp the total energy efficiency and light distribution depends on the design of the lighting system.Safety adviceNot suitable for operation with electronic control gear.Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.



April 13, 2020, 14:26:05 SubstiTUBE U-Shape

| Technical data | | | |
|-------------------------|---|---|--|
| | Electrical data | | Addition al product data |
| Product description | Max. lamp no. on circuit break. 10 A (B) | Max. lamp no. on circuit break. 16 A (B) | Appropri ate disposal acc. to WEEE |
| ST8U-EM 8 W/840 300 mm | 170 | 270 | Yes |
| ST8U-EM 20 W/840 600 mm | 75 | 120 | Yes |

Application advice

For more detailed application information and graphics please see product datasheet.

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|-------------------------|------------------------------|--------------------------------------|-----------------------|--------------|
| 4058075284685 | ST8U-EM 8 W/840 300 mm | Shipping carton box 10 | 332 mm x 256 mm x 182 mm | 15.47 dm³ | 1423.00 g |
| 4058075284708 | ST8U-EM 20 W/840 600 mm | Shipping carton box 10 | 616 mm x 252 mm x 180 mm | 27.94 dm ³ | 2587.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH Marcel-Breuer-Strasse 6 80807 Munich, Germany