

Product datasheet

P LINE R7s 150 15 W/827 R7s

PARATHOM LINE R7s | Double-ended special LED lamps



- Hospitality
- Domestic applications
- Outdoor applications only in suitable luminaires

- Long lifetime of up to 15,000 h
- Low energy consumption
- Four year guarantee
- Good all-around light emission
- Fits into most R7s luminaires thanks to excentric base

Product features

- LED alternative to conventional R7s lamps

Product benefits

- Long lifetime of up to 15,000 h
- Low energy consumption
- Four year guarantee
- Good all-around light emission
- Fits into most R7s luminaires thanks to excentric base



Product datasheet

Areas of application

- Hospitality
- Domestic applications
- Outdoor applications only in suitable luminaires

Technical data

Electrical data

Rated wattage	15.00 W
Nominal wattage	15.00 W
Nominal voltage	220...240 V
Operating frequency	50/60 Hz
Claimed equiv. conventional lamp power	125 W


Photometrical data

Nominal luminous flux	2000 lm
Rated luminous flux	2000 lm
Rated color temperature	2700 K
Color rendering index Ra	≥80
Light color (designation)	Warm White
Standard deviation of color matching	≤6 sdc _m
Lumen main.fact.at end of nom.life time	0.70

Light technical data

Starting time	< 0.5 s
---------------	---------

Dimensions & weight



Overall length	118.0 mm
Diameter	29.0 mm
Outer bulb	-
Length	118.0 mm

Lifespan

Nominal lamp life time	15000 h
------------------------	---------

Product datasheet

Rated lamp life time	15000 h
Number of switching cycles	100000
Lumen maintenance at end of service life	0.70

Additional product data

Base (standard designation)	R7s
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Clear
Appropriate disposal acc. to WEEE	Yes

Capabilities

Dimmable	No
----------	----

Certificates & standards

Energy efficiency class	A++
Energy consumption	15 kWh/1000h

Country specific categorizations

ILCOS	DRDG-15/827-230-R7s-114,2
Order reference	LEDPLI118125 15

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075812130	P LINE R7s 150 15 W/827 R7s	Shipping carton box 20 Pieces Folding carton box	159 mm x 129 mm x 131 mm	2.69 dm ³	1934.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany