# Candle Filament Flame Tip Omni Lamp B22 2W (25W) 2700K 230Im Non-Dimmable 300 deg Beam Angle



Integral Filament Omni Lamps utilise Filament LED technology and a full-glass body to create a decorative look and wide beam angle that looks fantastic in chandeliers and fittings where the lamp is exposed. The flame-like shape and warm light creates a pleasing candle-like effect.

These retrofit lamps are highly efficient and are an ideal replacement for traditional tungsten filament bulbs.

## **Product Details**

Partcode: ILCANDB22N045 Check Code: 487399 Range Name: Omni Market Segment: Commercial indoor, Residential indoor Product Type: Candle Warranty: 2 Years CE / RoHS: Yes

## **Physical Data**

Lamp Base: B22 Base Type: Bayonet cap Globe Type: Candle Globe Finish: Clear Material: Aluminium, Glass Construction: Glass shell, filament strip, Aluminium Base

## www.integral-led.com

Partcode: ILCANDB22N045 / Page: 2

#### **Physical Data**

Length: 111mm Width: 35mm Diameter: 35mm Weight (Unpackaged Single Unit): 19g Lamp or Luminaire Shape: Oval Lamp Fixing: Pendant, Wall

#### **Electrical Data**

Voltage Range: 220-240V Power Consumption: 2.0 Watts Driver included: Yes Electric Current: AC Ampage: 20.00mA Frequency Range: 50 Hz Power Factor: >=0.40 Wattage Equivalent: 25 Watts Dimming: Non-dimmable LVD Certified: Yes EN: EN-62560


## **Light Data**

Lumens: 230lm Lumens per Watt: 115.0lm/W Beam Angle: 300° Correlated Colour Temperature (CCT): 2700k Colour Temperature: Warm Colour Rendering Index (CRI): >=80 LED Type: Filament chip Instant on - Less than 1 second: Yes Lifetime: 15,000 hrs Switching Cycles: >7,500 X

## www.integral-led.com



Partcode: ILCANDB22N045 / Page: 3



Energy Rating: A++ Lowest Operating Temperature: -20 degrees Maximum Operating Temperature: 45 degrees IP (Ingress Protection) Rating: IP20 Hg 0% (Mercury Free): Yes

## **Packaging**

EAN Barcode (unit of 1): 5055788223177 Packaged Weight (Unit of 1): 69g Length (unit of 1): 42mm Width (unit of 1): 42mm Depth (unit of 1): 114mm **Outer packaging info available on website** 

Product data last updated on: Tuesday, September 8, 2020 - 22:12

### www.integral-led.com