# GU10 PAR16 4.7W (53W) 2700K 410Im Non-Dimmable Lamp - 5 PACK

Partcode: ILGU10NC089-5 / Page: 1



The Integral LED Classic GU10 range offers a fantastic ratio of value and performance. By incorporating a stylish engineered lens in an affordable GU10, the Classic offers directional light with a beam angle that closely mirrors that of familiar halogen lamps along with all the energy-saving and long-life benefits of LED.

### **Product Details**

Partcode: ILGU10NC089-5 Check Code: 271053 Range Name: Classic Placement / Application: Indoor, General Lighting Market Segment: Commercial indoor, Residential indoor Product Type: GU10 Warranty: 2 Years CE / RoHS: Yes

### **Physical Data**

Lamp Base: GU10 PAR16 Base Type: GU10 Base Colour: Matt white Product Finish: Matt white Spot Type: SMD with "COB like effect" Optic: Designed to give a Classic Look Material: Plastic and Aluminium heat-sink, Injection moulded diffuser Construction: Plastic White and "Classic look" diffuser lens

### www.integral-led.com

# integral LED

Partcode: ILGU10NC089-5 / Page: 2

#### **Physical Data**

Length: 54mm Width: 50mm Weight (Unpackaged Single Unit): 33g Lamp or Luminaire Shape: Round Lamp Fixing: Downlight

#### **Electrical Data**

Voltage Range: 220-240V Power Consumption: 4.7 Watts Driver included: Yes Driver IC Manufacturer: Bright Power Semiconductor Electric Current: AC Ampage: 40.00mA Frequency Range: 50/60 Hz Power Factor: >=0.40 Wattage Equivalent: 53 Watts Dimming: Non-dimmable LVD Certified: Yes EN: EN-62560

### **Light Data**

Useful Lumens: 370lm (Rated luminous flux in a 90° cone) Lumens: 410lm Lumens per Watt: 87.0lm/W Peak Intensity: 700Cd Beam Angle: 36° Correlated Colour Temperature (CCT): 2700k Colour Temperature: Warm Colour Rendering Index (CRI): >=80 LED Type: Surface mounted device (SMD) LED Size: 2835 Instant on - Less than 1 second: Yes Lifetime: 15,000 hrs Switching Cycles: >7,500 X

### www.integral-led.com



Partcode: ILGU10NC089-5 / Page: 3

#### **Environmental**



Energy Rating: A+ Lowest Operating Temperature: -20 degrees Maximum Operating Temperature: 40 degrees IP (Ingress Protection) Rating: IP20 Hg 0% (Mercury Free): Yes

## Packaging



EAN Barcode (unit of 1): 5055788230359 Packaged Weight (Unit of 1): 200g Length (unit of 1): 59mm Width (unit of 1): 103mm Depth (unit of 1): 103mm **Outer packaging info available on website** 

Product data last updated on: Wednesday, September 11, 2019 - 17:02

#### www.integral-led.com