# MR16 GU5.3 8.3W (51W) 4000K 700lm Non-Dimmable

Partcode: ILMR16NE036 / Page: 1



The Integral LED Classic MR16 range offers a fantastic ratio of value and performance. By incorporating a stylish engineered lens in an affordable spotlight, the Classic offers directional light with a beam angle that closely mirrors that of familiar halogen lamps along with all the energy-saving and long-life benefits of LED.

## **Product Details**

Partcode: ILMR16NE036 Check Code: 334380 Range Name: Classic Placement / Application: Indoor, General Lighting Market Segment: Commercial indoor, Residential indoor Product Type: MR16 Warranty: 2 Years CE / RoHS: Yes

## **Physical Data**

Base Type: GU5.3 Base Colour: Matt white Product Finish: Matt white Spot Type: SMD with "COB like effect" Optic: Designed to give a Classic Look Material: Plastic and Aluminium heat-sink, Injection moulded diffuser Construction: Plastic White and "Classic look" diffuser lens

## www.integral-led.com

Partcode: ILMR16NE036 / Page: 2

#### **Physical Data**

Length: 45mm Diameter: 50mm Weight (Unpackaged Single Unit): 45g Lamp or Luminaire Shape: Round Lamp Fixing: Downlight

#### **Electrical Data**

Voltage Range: 12V Power Consumption: 8.3 Watts Driver included: No, needs 12V AC Transformer Driver IC Manufacturer: Silergy Electric Current: AC Ampage: 700.00mA Frequency Range: 50 Hz Power Factor: >=0.90 Wattage Equivalent: 51 Watts Dimming: Non-dimmable LVD Certified: Yes EN: EN-62560

## **Light Data**


Useful Lumens: 640lm (Rated luminous flux in a 90° cone) Lumens: 700lm Lumens per Watt: 84.0lm/W Peak Intensity: 1,600Cd Beam Angle: 36° Correlated Colour Temperature (CCT): 4000k Colour Temperature: Cool White Colour Rendering Index (CRI): >=80 LED Type: Surface mounted device (SMD) LED Size: 2835 Instant on - Less than 1 second: Yes Lifetime: 15,000 hrs Switching Cycles: >7,500 X

## www.integral-led.com



Partcode: ILMR16NE036 / Page: 3

#### **Environmental**



Energy Rating: A+ Lowest Operating Temperature: -20 degrees Maximum Operating Temperature: 40 degrees IP (Ingress Protection) Rating: IP20 Hg 0% (Mercury Free): Yes

## Packaging

EAN Barcode (unit of 1): 5055788230694 Packaged Weight (Unit of 1): 65g Length (unit of 1): 60mm Width (unit of 1): 55mm Depth (unit of 1): 55mm **Outer packaging info available on website** 

Product data last updated on: Tuesday, September 8, 2020 - 22:14

#### www.integral-led.com