

NiMH Accus 4.0 Ah

Nickel-Metal Hydride cells (NiMH)



Product description

- _ High-temperature NiMH cells for use with emergency lighting units
- _ 4 year design life
- _ 1 year guarantee from delivery date

Properties

- _ Cadmium free
- _ Constant high-temperature operation – depending on the emergency lighting unit used (refer to respective emergency control gear data sheet)
- _ Low profile cross-section 21 mm
- _ Good charging properties at high temperature
- _ High energy maintenance of the charged battery
- _ Certified quality manufacturer
- _ In various configurations
- _ Simple connection with plug-in system
- _ With polycarbonate fixing caps
- _ Suitable for emergency lighting equipment as per IEC 60598-2-22


Website

<http://www.tridonic.com/89800438>



NiMH Accus 4.0 Ah

Nickel-Metal Hydride cells (NiMH)



Ordering data

Type	Article number	Number of cells	Capacity	Packaging, carton	Packaging, outer box	Weight per pc.
NiMh cells – stick + stick, 4 Ah						
Accu-NiMH 4Ah 4C CON	89800438	4	4 Ah	5 pc(s).	25 pc(s).	0.347 kg

Technical data

Battery voltage per cell	1.2 V
Min. battery casing temp. (design life of 4 years)	+ 5 °C
Max. battery casing temp. (design life of 4 years)	Refer to emergency control gear datasheet

Standards

according to EN 60598-2-22

Specific technical data

Type	Article number	Number of cells	Capacity y	Length L	Hole spacing D	Width B	Height H
NiMh cells – stick + stick, 4 Ah							
Accu-NiMH 4Ah 4C CON	89800438	4	4 Ah	204 + 204 mm	194 + 194 mm	22 mm	21 mm